



MONTAGE-ANLEITUNG

Picatinnyrail - für Heckler & Koch SL7 | HK630 | HK770 | HK940



1
Systemhülse laut Herstellerangabe demontieren. (Inbus 5mm)



2
Schutzblech entfernen.



3
Schiene aufsetzen.



4
Systemhülse mit aufgesetzter Schiene umdrehen und Nutsteine einlegen.



5
Schrauben (M4x8) anschrauben, dabei Schiene nach vorne drücken. Torx T20 | 3 Nm
Schraubenlänge beachten! Schrauben dürfen nicht aus dem Nutstein hervorstehen.
Systemhülse nach Herstellerangabe wieder montieren. (Inbus 5mm)





INSTALLATION MANUALL



Picatinnyrail - for Heckler & Koch SL7 | HK630 | HK770 | HK940



1 Remove receiver top cover according to manufacture´s instruction. (5mm Allen hey)



2 Remove the cover plate.



3 Align the rail on the top cover.



4 Turn the top cover with attached rail around and insert the clamping block.



5 Tighten the screws (M4x8) while pressing the rail forward. Torx T20 | 3 Nm
Mind the srew length! Screws must not protrude from the clamping block.
Reattach the reciever top cover according to manufacture´s instruc-tion. (5mm Allen key)

